


SUPER NOBELAIR®

Classic



- 1 Flexible beige PVC
- 2 Polyester reinforcement
- 3 Flexible black PVC

HOSE FOR COMPRESSED AIR SUPPLY.

Three layer design, in extra flexible PVC, with high resistant polyester fibre reinforcement.

APPLICATIONS

Pneumatic tools, equipment of assembly workshops, wall mounted reels, carts and compressors

SECTORS OF ACTIVITY

Automotive industry, plastics industry, assembly factories, garages (for cars, lorries and agricultural vehicles), woodwork

MARKING

SUPER NOBELAIR  20 BAR [Batch number]

ADVANTAGES

The balanced reinforcement of SUPER NOBELAIR® enables it to withstand high pressure with minimal distortion. Thus, it can withstand extended and frequent pressure impulse cycles.

The composition of this flexible and light hose provides it with good resistance to impacts and distortion.

Moreover, the PVC composition eliminates any risks of cracks appearing (particular defect of rubbers), thus improving safety and a long service life.

CONNECTORS







Quick connectors, barbed or serrated connectors.

Band, worm drive, screw or butterfly clamps.

Swaged fittings can be used if they do not damage the hose.

CHEMICAL RESISTANCE

[See table pages 106 to 109 column A.](#)

	+/- mm		+/- mm		g/m				Beige		
									25 m	50 m	100 m
6.3	+/-0.3	11	+/-0.3	2.35	85	60	20	45		Available	
7	+/-0.4	12	+/-0.4	2.5	90	60	20	49	Available		
8	+/-0.4	13	+/-0.4	2.5	107	60	20	56	Available	Available	071563
9	+/-0.5	14.5	+/-0.5	2.75	132	60	20	63	Available	071368	
10	+/-0.5	15.5	+/-0.5	2.75	143	60	20	70	Available	Available	Available
12.7	+/-0.6	19	+/-0.6	3.15	205	60	20	89	Available	Available	
16	+/-0.6	23	+/-0.6	3.5	284	60	20	112	071369	Available	Available
19	+/-0.8	26.5	+/-0.8	3.75	352	60	20	145	Available	Available	