


GAINÉ GA1

300
200
mbar

+60
-15
°C

Flexible ducting in PVC for ventilation and fumes suction. Reinforced with a rigid PVC spiral.



- 1 Spiral in rigid PVC
- 2 Wall in soft blue PVC

APPLICATIONS

- Ventilation
- Suction of air and fumes

SECTORS OF ACTIVITY

- Industry

Marking

GA1 Ø inn [Batch number]

ADVANTAGES

Ducting G.A.1 is very light and high flexible. Its smooth inner wall assures low flow losses.

CONNECTORS

Connectors with wire collars or screwed fittings (left hand spiral).

CHEMICAL RESISTANCE

See table pages 104 to 107 column A.

| mm | +/- mm | mm | mm | g/m | mbar | mm | Blue 30 m |
|----|---------|-----|------|-----|------|----|--------------|
| 25 | +/- 0,8 | 0,5 | 2 | 130 | 300 | 25 | 071319 |
| 30 | +/- 0,8 | 0,5 | 2 | 150 | 300 | 30 | 071320 |
| 35 | +/- 1,0 | 0,5 | 2,25 | 180 | 300 | 35 | |
| 38 | +/- 1,0 | 0,5 | 2,25 | 200 | 300 | 38 | |
| 40 | +/- 1,0 | 0,5 | 2,4 | 210 | 200 | 40 | |
| 50 | +/- 1,2 | 0,5 | 2,6 | 340 | 200 | 50 | 071321 |
| 63 | +/- 1,2 | 0,5 | 3 | 425 | 200 | 63 | |