

SUPER NOBELAIR® SOFT



60

+60
-20 °C

Highly flexible hose for compressed air.

Three layers, in extra-flexible PVC, with high strength polyester reinforcement.



- 1 Extra-flexible blue PVC
- 2 Polyester reinforcement
- 3 Extra-flexible black PVC

APPLICATIONS

- Pneumatic tools
- Equipment of assembly workshops, wall mounted reels, carts and compressors

SECTORS OF ACTIVITY

- Automotive industry
- Plastics industry
- Assembly factories
- Workshops for cars, lorries and agricultural vehicles
- Woodwork

Marking

SUPER NOBELAIR SOFT Ø inn x Ø out / Ø inn x th. 15 BAR  [Batch number]

ADVANTAGES

Compounds specially developed for SUPER NOBELAIR® SOFT give it a high flexibility even at low temperature. This property, associated with lightness, makes the use of this hose easier; therefore the hose is particularly appreciated by users of pneumatic tools both outdoors and indoors. PVC structure eliminates any risk of cracks (flaws of a lot of rubber hoses), making this hose long lasting.

Thanks to a well balanced reinforcement, SUPER NOBELAIR® SOFT has a high pressure resistance with little distortion under pressure. So it can withstand long and frequent impulse cycles.

CONNECTORS

Quick connectors, barbed or serrated grooved connectors. Band, worm drive, screw or butterfly clamps. Cap connectors. Swaged fittings can be used if they do not damage the hose.

CHEMICAL RESISTANCE

See table pages 104 to 107 column A.

mm	+/- mm	mm	+/- mm	mm	g/m	bar	bar	mm	Blue	
									25 m	50 m
6.3	+/-0.3	11	+/-0.3	2.35	81	60	15	45	available	available
8	+/-0.4	13	+/-0.4	2.5	106	60	15	56	available	available
9	+/-0.5	14.5	+/-0.5	2.75	131	60	15	63	available	available
10	+/-0.5	15.5	+/-0.5	2.75	141	60	15	70	available	available
12.7	+/-0.6	19	+/-0.6	3.15	200	60	15	89	available	available
16	+/-0.6	23	+/-0.6	3.5	265	60	15	112	available	available
19	+/-0.8	26.5	+/-0.8	3.75	337	60	15	145	available	available
25	+/-1.0	33.5	+/-1.0	4.25	493	60	15	210	available	available